



The AL-6326 offers a multitude of options and is perfectly suited to operating as a solo luminaire, being arranged to create patterns or as continuous lines of light.

KEY FEATURES

- Direct, extruded linear profile luminaire
- Suitable for surface mount or suspension fixing
- Finished in RAL 9006 grey as standard
- Available in 4 standard lengths
- Delivering approx. 2200 lm per meter as standard
- Coloured matched, injection moulded end caps
- TPA opal lens for feature, general and visual areas
- Low Glare prismatic lens available for office and LG7 compliance
- Tridonic low energy LED and driver system
- Life up to >72,000 hours L80/F10
- Efficacy up to 127 lm/tcW
- Manufactured in the U.K

Specification	
Power:	17.5W/25.2W/31.4W/50.5W
Voltage:	AC 220-240V
Work Temperature:	-25°C ~35°C/
Color Temperature:	3000K/4000K
CRI:	80
Weight:	2.5kg/3.5kg/4.3kg 7.3kg
IP Rate:	IP40
Warranty:	5 Years 2 Years Onsite

Ordering Information				
Model No	Length	Power	Lumens	Colour Temperature
AL-6326-001	850mm	17.5W	1725	3000K
AL-6326-002	850mm	17.5W	1825	4000K
AL-6326-003	1.2m	25.2W	2575	3000K
AL-6326-004	1.2m	25.2W	2725	4000K
AL-6326-005	1.5m	31.4W	3150	3000K
AL-6326-006	1.5m	31.4W	3325	4000K
AL-6326-007	2.5m	50.5W	5150	3000K
AL-6326-008	2.5m	50.5W	5425	4000K