
AL-6260 DOWNLIGHT

AURALED



Specification	
Power:	6.5W/8W/10W
Voltage:	AC 220-240V
Work Temperature:	-25℃ ~35℃ -25℃ ~25℃*
Color Temperature:	2700K/3000K/4000K
CRI:	80/90
Weight:	0.3g
IP Rate:	IP44 Front IP20 Rear
Warranty:	5 Years



KEY FEATURES

- Low glare architectural downlight
- Discreet minimal bezel, die-cast from pure aluminium
- Matt black darklight ba e, developed to minimise glare
- Fitted with an integral IP44 protective lens as standard
- Precision moulded 40° reflector
- Tridonic LED engine and driver system
- Excellent thermally optimised 24 super-fin die-cast heatsink
- Short circuit, overload and temperature protection

Ordering Information				
Model No	Lumens	Power	Colour	Colour Temperature
AL-6260-001-2.7K	600	8W	927	2700K
AL-6260-002-3K	675	6.5W	830	3000K
AL-6260-003-4K	700	6.5W	840	4000K
AL-6260-004-2.7K*	850	10W	927	2700K
AL-6260-005-3K*	850	8W	830	3000K
AL-6260-006-4K*	900	8W	840	4000K

IP**44**/IP**20**

WARRANTY: **5 YEARS**

CE RoHS compliant