



VX LED SPECIFICATION

CAT No	Colour Temp (K)	Colour Rendering (RA)	Life (hrs)	Total Delivered Lumens (lm)	Connected Load Total (tcw)	Luminaire System Efficacy (lm/W)
AL-VX2184	4000	80	60000	2570	21	122
AL-VX2484	4000	80	60000	2827	24	118
AL-VX3084	4000	80	60000	3470	30	116
AL-VX3484	4000	80	60000	3810	34	112
AL-VX3884	4000	80	60000	4050	38	107
AL-VX2183	3000	80	60000	2390	21	114
AL-VX2483	3000	80	60000	2690	24	112
AL-VX3083	3000	80	60000	3300	30	110
AL-VX3483	3000	80	60000	3570	34	105
AL-VX3883	3000	80	60000	3870	38	102

- VX LED for 500 x 500 and 600 x 600 grid ceiling
- Microprism optic or matt opal, fully recessed body with no protrusion below Ceiling grid line
- Glare-free lighting -UGR19
- The balanced contrast creates a pleasant atmosphere, illumination that complies with current standard

- LG7 high light output, balanced with good quality lit environment
- It eliminates dark ceilings
- Fits exposed T-bar 15 or 25mm

- Housing fabricated from cold-rolled steel high-reflectance powder coated matt white
- Conforms to *EN 12464-1 UGR<19 LG7:2015 <3000 cd/m2 @ 65° -
- Microprismatic central optic for glare-free illumination

CE

- Opal central optic for enhanced light transmission and perfect uniform illuminations



- Air handling to 25 L/S
- Tridonic LED modules
- Tridonic LED driver
- TPa
- L90/60,000hrs B10
- 3 Step MacAdam Ellipse

1 Year on site warranty




Options

- DSI dimmable
- DALI
- 3 hour emergency version
- Self emergency
- DALI addressable emergency
- Turnable White LED module with 2,700 and 6,500 K



VX micro prism



VX opal

Add suffix to catalogue number:

HFD: Dimmable. **HFDD** DALI. **EM3:** Emergency version **STE:** Self test emergency. **DE3:** DALI emergency. **MP:** Micro prism. **MO:** Matt opal optic.

