



Specification	
Input Voltage	150 TO 250 AC
Input Frequency (Hz)	50-60
Drivers	INCLUDED
CRI	≥80
Beam Angle	120°
Life (H)	30000
Operating Temperature (°c)	-25 to 50
IP Rating	IP40
Warranty	3 Years

Physical Data	
Shape	SQUARE/ RECTANGLE
Colour	WHITE
Finish	ALUMINIUM



KEY FEATURES

- Ultra low power from 18w
- Steel Backed
- Upto 70% of energy savings
- Recessed/Surface
- Suspended Available
- Slim aluminium edge frame
- Dimmable and Emergency Optional
- Adjustable Wattages

Ordering Information

Part Number	Power (W)	Lumen	Depth (mm)	Height (mm)	Width (mm)	Colour Temp
AL-ECO-600X600-18W-40/60	18	1595/1890	11	595	595	4000/6000
AL-ECO-600X600-22W-40/60	22	1925/2310	11	595	595	4000/6000
AL-ECO-600X600-30W-40/60	30	2600/3150	11	595	595	4000/6000
AL-ECO-600X600-36W-40/60	36	3150/3780	11	595	595	4000/6000
AL-ECO-600X600-48W-40/60	48	4200/4620	11	595	595	4000/6000
AL-ECO-1200X600-44W-40/60	44	4180/4620	11	1195	595	4000/6000
AL-ECO-1200X600-60W-40/60	60	5700/6300	11	1195	595	4000/6000
AL-ECO-1200X600-72W-40/60	72	6840/7560	11	1195	595	4000/6000