

Specification		
LED Light source	High Power LED	
Light Color	RGB, CW, WW, NW	
Material	SUS316	
Optics	S10° / F40°	
Power	8w	
Power supply	24v	
Dimension	96 x 47	
Weight	940g	
IP Rating	IP68	
Approvals	CE,RoHS,IP	
Ambient temperature	-20°C ~ +45°C	
Average life	50,000 Hrs	
Accessories (optional)	Yes	
Applications	Indoor /Outdoor /Landscape / Submersible	



KEY FEATURES

Midsize surface fixture complete with integral CREE XPE LED (8pcs LED) package and 10/40 degree beam options. Tempered glass,marine-grade 316 Stainless Steel construction rated to IP68. Hidden & embedded design installation. No mechanical joints to light source ensure robust protection against water ingress. The product runs cool meeting all touch temperature requirements. Inline 350mA driver options include switched, mains, 1-10V, DALi dimmable and AuraSmart compatible solutions.





Ordering Information				
Model No	LED Brand	Colour	Description	
AL-GL068 WW	CREE	3000K	8W 10/40* GROUND IP68 24V 316	
AL-GL068 NW	CREE	4000K	8W 10/40* GROUND IP68 24V 316	
AL-GL068 CW	CREE	6000K	8W 10/40* GROUND IP68 24V 316	
AL-GL068 RGB	CREE	RGB	8W 10/40* GROUND IP68 24V 316	

