




Specification	
Working Voltage:	AC100~240V or 3V (AAA * 2PCS) / DC3.3V
RF:	2.4GHz
Work Temperature:	-20~60°C
Modulation Method:	GFSK
Transmission Frequency:	2400-2483.5MHz
Control Distance:	30m
Transmitting Power:	6dBm
Warranty:	3 Yrs



WARRANTY: 3 YEARS

AL-WALLRGB-CCT



AL-WALLRGB-CCT-MAINS



AL-WALLPAN8Z



AL-WALLPAN8Z-MAINS



AL-WALLSC4Z



AL-WALLSC4Z-MAINS



KEY FEATURES

- High precision capacitive touch IC
- 2.4GHz RF Wireless transmission technology
- Control distance: 30m
- Battery and Mains powered options

Ordering Information

Model No	Description
AL-WALLRGB-CCT	4-Zone RGB+CCT Smart Panel Battery Operated
AL-WALLRGB-CCT-MAINS	4-Zone RGB+CCT Smart Panel Mains Operated
AL-WALLPAN8Z	8 Zone Wall Controller RGB-CCT Battery Operated
AL-WALLPAN8Z-MAINS	8 Zone Wall Controller RGB-CCT Mains Operated
AL-WALLSC4Z	Single Colour 4 Zonel Wall Panel Battery Operated
AL-WALLSC4Z-MAINS	Single Colour 4 Zonel Wall Panel Mains Operated

