



The AL-6346 is available in four lengths and can be used to create seamless lines of light

KEY FEATURES

- Continuous direct, extruded linear profile system
- Features through wiring for simple electrical connection
- Mechanical joining kit with every product
- Start / End piece includes end cap
- Available in 4 building block lengths
- Suitable for surface mount or suspension fixing
- Finished in RAL 9006 grey as standard
- TPa opal lens for general and visual areas as standard
- Low glare prismatic lens available for office and LG7 compliance
- Tridonic low energy LED and driver system
- L80/F10 >72,000 Hrs
- Manufactured in the U.K.

Specification	
Power:	17.5W/25.2W/31.4W/ 50.5W
Voltage:	AC 220-240V
Work Temperature:	-25°C ~35°C/
Color Temperature:	3000K/4000K
CRI:	80
Weight:	2.5kg/3.5kg/4.3kg 7.3kg
IP Rate:	IP40
Warranty:	5 Years 2 Years Onsite

Ordering Information				
Model No	Length	Power	Lumens	Colour Temperature
AL-6346-001	850mm	17.5W	1725	3000K
AL-6346-002	850mm	17.5W	1825	4000K
AL-6346-003	1.2m	25.2W	2575	3000K
AL-6346-004	1.2m	25.2W	2725	4000K
AL-6346-005	1.5m	31.4W	3150	3000K
AL-6346-006	1.5m	31.4W	3325	4000K
AL-6346-007	2.5m	50.5W	5150	3000K
AL-6346-008	2.5m	50.5W	5425	4000K