



KEY FEATURES

- VX LED for 500 x 500 and 600 x600 grid ceiling
- Microprism optic or matt opal, fully recessed body with no protrusion below Ceiling grid line
- Glare-free lighting -UGR19
- The balanced contrast creates a pleasant atmosphere, illumination that complies with current standard
- LG7 high light output, balanced with good quality lit environment
- It eliminates dark ceilings
- Fits exposed T-bar 15 or 25mm
- Housing fabricated from cold-rolled steel high-reflectance powder coated matt white Conforms to *EN 12464-1 UGR<19 LG7:2015 <3000 cd/m2 @ 65°
- Microprismatic central optic for glare-free illumination
- Opal central optic for enhanced light transmission and perfect uniform illuminations
- Air handling to 25 L/S
- Tridonic LED modules
- Tridonic LED driver
- TPa
- L90/60,000hrs B10
- 3 Step MacAdam Ellipse
- Casambi Wirefree Controls also available

Specification	
Power:	21W - 38W
Voltage:	AC 220-240V
Life L90 Hrs	60000
Color Temperature:	3000K /4000K
CRI:	80
Warranty:	5 Years

Ordering Information				
Model No	Lumens	Power	Life Hrs	Colour Temperature
AL-VX2184	2570	21W	60000	4000K
AL-VX2484	2827	24W	60000	4000K
AL-VX3084	3470	30W	60000	4000K
AL-VX3484	3810	34W	60000	4000K
AL-VX3884	4050	38W	60000	4000K
AL-VX2183	2390	21W	60000	3000K
AL-VX2483	2690	24W	60000	3000K
AL-VX3083	3300	30W	60000	3000K
AL-VX3483	3570	34W	60000	3000K
AL-VX3883	3870	38W	60000	3000K

WARRANTY: **5 YEARS**

