



Optic flexible wall washer LED strip - IP67
 Input Voltage:24V DC
 Power:19.2W/m(Symmetric),16W/m(Asymmetric)
 Single CCT: 2500K/ 2700K/3000K/3500K/4000K/6500K;
 Tunable white CCT:2700K-6500K;
 DMX control:
 1.DMX single CCT 2500K/ 2700K/3000K/3500K/4000K/6500K;
 2.DMX Tunable white CCT 2700K-6500K;
 3.DMX RGB;
 Beam angle: 20°/30°/40°/50°/25° X 40°,70° x 110°(Asymmetric),
 35°/50°/45°X55°(RGB/RGBW)


Cuttable
 Maximum 5 meters
 Application: suit for commercial lighting,
 wall washing illumination
 Working Temperature:-40°C~+45°C
 Net weight :240g/meter (Symmetric)
 220g/meter (Asymmetric)

The above net weight does not include aluminum profiles.
 For outdoor application, must be used together with aluminum
 housing for heat release.


suit for class 2 power unit, maximum connected power not more than 100W




Part No.	Description	Picture	Part No.	Description	Picture
1.05.025.0225 (1.046m) 1.05.025.0224 (2.046m) 1.05.025.0227 (3.16m)	Aluminum profile		2.03.LL.0002	2 PIN Female Connection Cable	
1.01.04.25.0004 1.01.05.0277 (M2.6*8mm)	End cap- E1 Self-tapping screws		2.03.LL.0001	2 PIN Male Connection Cable	
1.01.04.25.0005 1.01.05.0277 (M2.6*8mm)	End cap- E2 Self-tapping screws		2.03.LL.0010	2 PIN Female Connection Cable from Left Side	
1.04.02.25.0014 (1.046m) 1.04.02.25.0013 (2.046m) 1.04.02.25.0017 (3.16m)	PC37-30 PC COVER -P1		2.03.LL.0009	2 PIN Male Connection Cable from Right Side	
1.04.02.25.0007 (3.02m)	FP06-30 PC COVER -P2		2.03.LL.0003	2 PIN join connector	
1.01.07.0091 1.01.05.0030 (M3*16mm)	Stainless steel mounting clip Self-tapping screws		2.03.LL.0012	End cap	
1.01.07.0101 1.01.05.0296 (M3*16mm) 1.01.05.0218 (M3*3mm)	90 degree turnable clip Self-tapping screws		1.11.01.0098	UV glue	
1.13.13.0247	UV light				



20°(Symmetric)



25° X 40°(Symmetric)



70° x 110°(Asymmetric)