




Part No.	Description	Picture	Part No.	Description	Picture
1.05.005.0014 (1m) 1.05.005.0015 (2m) 1.05.005.0016 (3m)	Aluminum profile		1.02.04.05.0014 (with hole)	End cap PC white	
			1.02.04.05.0015 (w/o hole)		
			1.05.005.0040 1m 1.05.005.0041 2m 1.05.005.0042 3m	Aluminum plate	
1.16.005.0040 (1m) 1.16.005.0041 (2m) 1.16.005.0042 (3m)	PMMA one time extrusion profile		1.11.01.0079	EPOXY ADHESIVE	

IP67 LED Profile  
 Dimension: W20.2\*H16.2\*L1000mm  
 (Customized length is available on request.)  
 Input voltage:24V DC  
 Power: 10W/meter  
 120pcs LED per meter  
 Color Temperature: 2400-6500K  
 CRI:≥80  
 (CRI more than 80 is available on request )  
 Beam Angle: 110°  
 Cable length: 200mm  
 (Option : Cable comes from the side,from the end,from the bottom)  
 IP rating: IP67  
 Working Temperature:-40°C~+45°C  
 Net Weight:451g/meter  
 Fire rating:HB

Application: suit for indoor or outdoor light decoration  
 suit for class 2 power unit, maximum connected power not more than 100W



Part No.	Description	Picture	Part No.	Description	Picture
1.05.005.0206 (1m) 1.05.005.0207 (2m) 1.05.005.0208 (3m)	Aluminum profile		1.02.04.05.0014 (with hole)	End cap PC white	
			1.02.04.05.0015 (w/o hole)		
			1.01.04.05.0001 1.01.05.0356 (M2.6*10)	End cap Self-tapping screws	
1.16.005.0040 (1m) 1.16.005.0041 (2m) 1.16.005.0042 (3m)	PMMA one time extrusion profile		1.05.005.0040 1m 1.05.005.0041 2m 1.05.005.0042 3m	Aluminum plate	
1.11.01.0079			EPOXY ADHESIVE		

IP67 LED Profile  
 Dimension: W36.4\*H35\*L1000mm  
 (Customized length is available on request.)  
 Input voltage:24V DC  
 Power: 10W/meter  
 120pcs LED per meter  
 Color Temperature: 2400-6500K  
 CRI:≥80  
 (CRI more than 80 is available on request )  
 Beam Angle: 110°  
 Cable length: 200mm  
 (Option : Cable comes from the side,from the end,from the bottom)  
 IP rating: IP67  
 Working Temperature:-40°C~+45°C  
 Net Weight:750g/meter  
 Fire rating:HB

Application: suit for indoor or outdoor light decoration  
 suit for class 2 power unit, maximum connected power not more than 100W

