

AL-WP03AL3 (AP0502AL3) IP67/IP68 LED Linear Light



Part No.	Description	Picture	Part No.	Description	Picture
1.05.015.0325 (1m)	Aluminum profile		1.02.04.15.0019 (with hole)	Frosted end cap	
1.05.015.0324 (2m)			1.02.04.15.0020 (w/o hole)		
1.05.015.0323 (3.05m)					
1.16.005.0056 (1m)	PMMA one time extrusion profile		1.05.015.0034 1m	Aluminum plate	
1.16.005.0057 (2m)			1.05.015.0036 2m		
1.16.005.0058 (3m)			1.05.015.0037 3m		
1.11.01.0079	EPOXY ADHESIVE		1.01.04.05.0024	End cap	
			1.01.05.0345 (M3*10)	Self-tapping screws	

IP67/IP68 LED Profile  
 Dimension: W24.9\*H44\*L1000mm  
 (Customized length is available on request.)  
 Input voltage:24V DC  
 Power: 15W/meter  
 120pcs LED per meter  
 Color Temperature: 2400-6500K  
 CRI: ≥80  
 (CRI more than 80 is available on request)  
 Beam Angle: 110°  
 Cable length: 200mm  
 (Option : Cable comes from the side,from the end,from the bottom)  
 IP rating: IP67/IP68  
 Working Temperature:-40°C~+45°C  
 Net Weight:850g/meter  
 Fire rating:HB

Application: suit for indoor or outdoor light decoration  
 can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W

