




Part No.	Description	Picture	Part No.	Description	Picture
1.05.060.0022 (1M) 1.05.060.0021 (2M)	Aluminum profile		1.05.060.0030 (1M) 1.05.060.0031 (2M)	Aluminum plate	
1.16.060.0005 (3.2M)	PMMA one time extrusion profile		1.02.04.60.0006	Frosted end cap	
1.01.04.60.0002	End cap				
1.01.05.0345 (M3*10)	Self-tapping screws				

IP67/IP68 LED Profile
 Dimension: W45*H45*L1000mm
 (Customized length is available on request.)
 Input voltage:24V DC
 Power :30W/meter
 240pcs LED per meter
 Color Temperature: 2400-6500K
 CRI:≥80
 (CRI more than 80 is available on request)
 Beam Angle: 120°
 Cable length: 200mm
 (Option : Cable comes from the end,from the bottom)
 IP rating: IP67/IP68
 Working Temperature:-40°C~+45°C
 Net Weight:1987g/meter
 Fire rating:HB

Application: suit for indoor or outdoor light decoration
 can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W



Part No.	Description	Picture	Part No.	Description	Picture
1.05.060.0017 (1M) 1.05.060.0018 (2M) 1.05.060.0019 (3.02M)	Aluminum profile		1.05.060.0030 (1M) 1.05.060.0031 (2M)	Aluminum plate	
1.16.060.0005 (3.2M)	PMMA one time extrusion profile		1.02.04.60.0006	Frosted end cap	
1.01.04.60.0001	End cap				
1.01.05.0345 (M3*10)	Self-tapping screws				

IP67/IP68 LED Profile
 Dimension: W45*H80*L1000mm
 (Customized length is available on request.)
 Input voltage:24V DC
 Power: 30W/meter
 240pcs LED per meter
 Color Temperature: 2400-6500K
 CRI:≥80
 (CRI more than 80 is available on request)
 Beam Angle: 120°
 Cable length: 200mm
 (Option : Cable comes from the end,from the bottom)
 IP rating: IP67/IP68
 Working Temperature:-40°C~+45°C
 Net Weight:2437g/meter
 Fire rating:HB

Application: suit for indoor or outdoor light decoration
 can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W

