




| Specification | |
|---|------------------------|
| Input Voltage | 220 TO 240 AC |
| Wattage | 50W |
| Lumens | 6900LM |
| Class | Class 1 |
| Life (H) | 50000 |
| Operating Temperature (°c) | -10 to40 EM 0 to 40 |
| IP Rating | IP65 |
| Lumens P/Wat | 138 lm/W |
| Emergency Lumens | 179lm |
| CCT | 4000K |
| IK | IK08 |
| Warranty 7 Years + 1Yr on-site (Battery 3 years) | |



NCF NX LED NCF, 1.5m,50W, 6900LM, 4000K, IP65, narrow body

KEY FEATURES

- Narrow design with high efficiency opal diffuser
- UV stabilized body, IK08 impact rating
- Robust stainless steel clips

| Ordering Information | | | | | | |
|----------------------|-----------|--------|--------|---------|--------|--------|
| Part Number | Power (W) | Lumen | L (mm) | LF (mm) | W (mm) | H (mm) |
| Standard | | | | | | |
| AL-NCF/2X5/ST/GR/840 | 50W | 6900LM | 1485 | 1000 | 76 | 72 |
| Emergency | | | | | | |
| AL-NCF2X5/M3/GR/840 | 50W | 6900LM | 1485 | 1000 | 76 | 72 |