




Contemporary and stylish luminaire available in a range of outputs. Ideal for pedestrian areas, terraces and general open spaces.

- Die-cast aluminium housing with super white tempered glass and polycarbonate reflector.
- Optical lens offering visual comfort and uniform light distribution.
- High quality LED chips and DALI driver as standard, with in-built surge protection up to 20KV.
- Suitable for pole mounting on Ø60mm poles.
- UV protected pure polyester powder coated housing offering high corrosion resistance.
- Suitable for use with a range of controls and remote management systems.
- All external screws are 304 stainless steel as standard.
- RAL9005, other RAL colours available on request.




Optics


LED Optics T1/T1D



LED Optics T2A/T2D



LED Optics T2W



Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
VAS-S24	T1	16	3000/4000	3150/3320	>70	24W	IP66	IK09	9.3
VAS-S24	T2W			3120/3260					
VAS-S40	T1	24	3000/4000	5240/5410	>70	40W	IP66	IK09	9.3
VAS-S40	T2W			5160/5320					
VAS-S60	T1	24	3000/4000	6100/6550	>70	60W	IP66	IK09	9.3
VAS-S60	T2W			5980/6300					
VAS-S80	T1D	36	3000/4000	9660/10070	>70	80W	IP66	IK09	9.6
VAS-S80	T2D			9340/9840					


General Specification

Input voltage	220-240V
Input frequency	50/60Hz
Surge protection	20KV
LED Chips	Philips 5050
Lifetime	L70 100,000hours L80 70,000 hours L90 34,000 hours
SDCM	SDCM<6
Class	Class I
Ambient temperature	-20°C to +50°C
Material	High pressure die-cast aluminium housing with tempered glass
Finish	Polyester powder coat cured under heat
RAL colour	RAL9005

Driver Details

Product	VAS-S24	VAS-S40	VAS-S60	VAS-S80
Driver	Tridonic			
Dimming control	DALI			
Driver current	960mA	1050mA	800mA	810mA
Inrush current	14.88A, 226µs	24.88A, 236µs	32A, 355µs	41.6A, 238µs
Power factor	0.97	0.97	0.97	0.98

Dimensions



VAS